

GBR Manufacturing Request Checklist (Rev.07)



| | | | |
|---------------------------|--|-------------------|--|
| Customer Name : | | Date Submitted : | |
| Customer Address : | | Shipping Date : | |
| Email/ Contact No. : | | Customer PO No. : | |
| Agent Name : | | Agent PO No. : | |
| Agent Address : | | | |
| Email/ Contact No. : | | Machine No. : | |
| Getech Person-in-Charge : | | Work Order No. : | |

Please tick "Select" Column based on the selection.

| S/N | GBR Configuration & Features | Select (√) | Remarks |
|-----|----------------------------------|--|---------|
| 1 | Power supply | 208V (3 Phase+E) , 60Hz, Range 208~240V | |
| | | 415V (3 Phase+N+E) , 50Hz, Range 380~415V | |
| 2 | CE Conformance | Non CE (Default) | |
| | | CE* (Option) | |
| 3 | Machine Model | GBR 1000 | |
| 4 | Flow Direction | Left to Right (Default) | |
| | | Right to Left (Option) | |
| 5 | Conveyor | Flat Belt Out-going Conveyor L ~1.5m, W ~495mm, Belt-W ~415mm, L Outside GBR ~640mm. Detect tall components up to 30mm height (Default) | |
| | | Out-going Shutter Axis (with dedicated PCB carriage plate for small PCB) L ~1.6m, W Outside GBR ~545mm, L Outside GBR ~720mm (*Option) | |
| | | No conveyor (Option) | |
| | | Edge Belt Out-going Conveyor L ~1298mm, W ~496mm, L Outside GBR ~372mm. Bi-direction use with 909500NU1002 (MAX. W +MOTOR OUTSIDE GBR ~710mm) (*Option) | |
| | | Edge Belt Out-going Conveyor L ~1610mm, W ~450mm, L Outside GBR @ left / loading ~100mm, @ right / unloading ~260mm. Bridge Type Single-direction fixed across GBR use with 909500NU1005 & 909500NU1006 (MAX. W +MOTOR OUTSIDE GBR ~652mm) (*Option) | |
| 6 | Gripper jaws (Fingers & adapter) | Package A : GBRF290_x4, GBRF291_x8, GBRF2004_x4, GBRF2005_x4 (Default) | |
| | | Package B : GBRF290_x4, GBRF291_x8, GBRF2004_x4, GBRF2008_x4 (Option) | |
| | | Package C : GBRF2010_x4, GBRF2011_x4, GBRF2012_x8, GBRF2008_x4 (Option) | |
| | | Others (Option, choice of 5 type standard | |
| | | Customised gripper (*Option) | |
| 7 | PCB Dust Cleaning | PCB dust cleaning & switching valve (*Option) | |
| | | Bar Ionizer (*Option) | |

| S/N | GBR Configuration & Features | | Select (√) | Remarks |
|------------------------|--|---|------------|---------|
| 8 | Loader/ Unloader | M Size Single Magazine Loader (*Option) 909500NU1001 | | |
| | | Customized Belt Type FIFO, XL-Size (*Option) 909500NU1002 | | |
| | | NTM0501-L-1000-2 (S) Scan Conveyor, 1000mm, 2 Zones (*Option) 909500NU1003 | | |
| | | NTM 730LM Triple Magazine Line Loader (*Option) 909500NU1004 | | |
| | | Single Stack Tray Loader (*Option) 909500NU1005 | | |
| | | Single Stack Tray Unloader (*Option) 909500NU1006 | | |
| | | Others to be specified (*Option) | | |
| 9 | Capable for MES and GRMS connection | Total 6 LAN Port at IPC (Default) | | |
| 10 | Others (*Option) | | | |
| (*) Chargeable Options | | | | |