

GAR1200L GETECH AUTOMATIC ROUTER - L

TOTAL SOLUTION FOR ROUTER BUSINESS

As a world leader in PCB Depaneling systems, **GETECH** presents **GAR1200L**. An in-line machine designed for high-speed routing and high volume production of Large PCB panels (450mm x 310mm).



FEATURES

SINGLE LARGE TABLE

SMALL MACHINE FOOTPRINT

HIGH ACCURACY & QUALITY CUT

HIGH-SPEED ROUTING & THROUGHPUT

READY FOR IN-LINE AUTOMATION

HIGH-RESOLUTION CAMERA

AUTOMATIC TOOL CHANGE

SAFETY PROTECTION

POWERFUL DUAL VACUUM SYSTEM

USER FRIENDLY SOFTWARE

CE CERTIFICATION (OPTION)



ISO 9001 : 2015 Cert. No.: 622220

GAR1200L Getech Automatic Router - L

Local Agent:



The GAR1200L is an in-line router machine specially designed to route (depanelize) large panels with PCB sizes of 450mm x 310mm into individual units. It is a fast, space-saving, and accurate machine designed for high volume production with minimal operator participation. The superior servo axis system provides a high acceleration/deceleration, reducing cycle time (increase in production output) and at the same time maintaining high accuracy cutting.

Using a high-resolution CCD camera and GAR user-friendly Windows-based software allows users to program the routing paths in minutes. There are also no limitations in the number of programs stored. GAR1200L uses high-quality components and a welded steel structure to ensure rigidity and high performance. All the axes and linear guides used are protected from dust and dirt to increase lifespan and performance.

SPECIFICATIONS

Routing Capability	Non-Routing Speed	: 1000 mm/sec
	Routing Speed	: 100 mm/sec max (depending on material, cutting quality & tool diameter)
	Repeatability	: ±0.05 mm straight lines, curves, and interpolated profiles
Manipulator	Configuration	: X, Y, Z & E axis
	Manipulator Motors	: AC brushless servo motors
	Manipulator Repeatability	: ±0.02 mm
	Resolution	: ±0.01 mm
Workstation	Design	: Single large workstation with dedicated pin fixtures
	Panel Positioning	: Located by tooling holes or edges of PCB
	Panel Loading	: Automatic (In-line automation-ready)
	Panel Size	: L450 mm x W310 mm
	Panel Thickness	: 0.5 mm – 8.0 mm
	Component Height	: Top max. 10 mm, Total (Top + Bottom) max. 35mm
Spindle System	Spindle Motor	: 0.5 kW (60,000 rpm) spindle with ESD / Ceramic bearings
	Options	: 0.42 kW (100,000 rpm), 0.25 kW (60,000 rpm)
	Tool Change	: Auto-Tool Change (Available for 0.5 kW/0.42 kW Spindles)
	Cooling	: Ambient cooled
	Router bit	: Shank size 3.175 mm (1/8")
Dust Filtration System	Power	: 2 x 3.0 kW rotary vane vacuum blower
	Filtration	: 3 stage filtrations with disposable filter bag (10 microns)
	Vacuum Location	: Top vacuum on spindle
	Extraction Hose (x2)	: ID 51 mm (2"), L= 4M
Noise Level	: <78 dB	
Vision System	Video camera	: High resolution CCD video camera
Programming	System Platform	: Windows® based Industrial PC (Win 10)
	Product Setup	: Vision assisted point to point manual teaching; Vision assisted editing function; Test-run mode
	Variable Functions	: Tool life optimization, Barcode support (1D or 2D), Autoloading of last product, Tool bit diameter compensation, and Fiducial alignment. Other options are available.
Operation Monitor	Router Bit	: Tool life tracking, Tool breakage detection, Routed board count
	Vacuum	: Vacuum filter change alarm
	Machine	: Machine error history
Maintenance	Router Bit	: 100 to 300 M cutting distance before next tool change (depending on PCB)
	Filter Bag	: 1000 to 1500 M before next filter bag change
	Cleaning hose	: Extra hose for periodic internal cleaning included
Conveyor System	Incoming Conveyor	: Belt type edge conveyor
	Conveyor Width Adjustment	: Manual (Front rail – Fixed, Back rail – Manual adjust)
	Conveyor Direction	: Left to Right or Right to Left
	Communication	: SMEMA
	Offload module	: Customer specifications
Safety Features	E-stops, Spindle stop, Spindle motor overheat & Servo overload detection, Enclosed work area with safety doors	
Dimensions & Utilities	Machine Size (W x D x H)	: 1750 mm x 1450 mm x 1700 mm
	Vacuum Tank Size (Ø x H)	: 2 x 400 mm x 800 mm
	Weight (Main + 2 Tanks)	: Approx. 1000kg + 50Kg
	Power Supply	: 3+N+E, 380~415V, 50 Hz or 3+E, 208~240V, 60 Hz; 7kW
	Air Supply	: 6 bars